m:	,
This Space For Architect/Engineer App Job NameDate	
Model Specified Quantity	
Customer/Wholesaler	
Contractor	
Architect/Engineer	
GO" FLEXIBLE ST. STEEL HOSE ASM., 304 ST. STEEL OUTER HOSE 40" SELF-CLOSING SPRAY VALVE W/ HOLD-DOWN RING DIMENSIONS ARE APPROXIMATE	STAINLESS STEEL OVERHEAD SUPPORT SPRING W/ POLISH CHROME BRASS SPRING BODY 6" WALL BRACKET, POLISH CHROME BRASS FINGER HOOK, POLISH CHROME BRASS 8" NPT x 18" RISER; POLISH CHROME BRASS BASE FAUCET CONTAINS ¼ TURN CERAMIC CARTRIDGE SINK MOUNTING SURFACE 51 NPSM MALE SHANK, %" DIAMETER MTG. HOLE REQUIRED CHECK VALVE w/ ½" NPSM MALE THREAD
MODEL NUMBER	
5PR-1S00-60	3/21/06 1:8 DHL CHECKED JHB
e quip	SINGLE SUPPLY DECK MOUNT PRU 60" LONG FLEXIBLE HOSE

equip Foodservice Accessories P.O. BOX 1088, 2 SADDLEBACK COVE TRAVELERS REST, SOUTH CAROLINA 29690 PHONE: 800.891.4808 FAX: 800.868,0084