T&S

T&S BRASS AND BRONZE WORKS, INC.

2 SADDLEBACK COVE / P.O. BOX 1088 / TRAVELERS REST, SC 29690 PHONE 800-476-4103 - FAX 864-834-3518



Model No.

B-0113-01B

RELIABILITY BUILT IN

8/4/06

JHB

Architect/Engineer Approval: Job Name: Notes: EPAct2005 COMPLIANT HOSE, SPRING BODY, OVERHEAD SPRING & SPRAY VALVE COME PRE-45" ASSEMBLED. [1143mm] FINGER HOOK COMES B-0109-01 PRE-INSTALLED ONTO RISER. B-0107-C35 6" WALL ADJUST TO DESIRED LOW FLOW BRACKET POSITION IN FIELD ANGLE SPRAY VALVE 3/8" NPT x 24" RISER IS PRE-ASSEMBLED TO 16 9/16" LOCKING FITTINGS BELOW [421mm] 17 7/16" LOCK NUT & BUSHING. [442mm] SPRING CHECK CARTRIDGES w/ LEVER HANDLES 18" LONG FLEXIBLE STAINLESS STEEL SUPPLY APPX. 22" HOSES. [559mm] SIDE VIEW COMPRESSION FITTINGS FOR 5/8" O.D COPPER TUBING, or REMOVE COMPRESSION NUT FOR 1/2" NPSM MALE. * DIMENSIONS MAY VARY $\pm 1/2$ " ON EACH INSTALLATION FRONT VIEW Product Description: Drawn: Checked Scale: EASY INSTALL PRE-RINSE UNIT: DHL WJS 1:8 SINGLE DECK MOUNT BASE MIXING FAUCET, FLEXIBLE SUPPLY HOSES, Approved Date:

24" RISER, SUPPORT SPRING, 44" FLEX HOSE, B-0107-C35 ANGLE LOW FLOW SPRAY VALVE